

VMware® VMmark® V2.5.1 Results

Vendor and Hardware Platform: Dell PowerEdge R820
Virtualization Platform: VMware ESX 4.1.0 U3 Build 800380
VMware vCenter Server : VMware vCenter Server 5.1.0 Build 799731

**VMmark V2.5.1 Score =
19.79 @ 18 Tiles**

Number of Hosts: 2

Uniform Hosts [yes/no]: yes

**Total sockets/cores/threads in test:
8/64/128**

Tested By: Dell Inc.

Test Date: 08-12-2013

Performance Section
[Performance](#)

Configuration Section
[Configuration](#)

Notes Section
[Notes for Workload](#)

Performance

	mailserver			olio			dvdstoreA			dvdstoreB			dvdstoreC			
TILE_0	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.05	0.98	53.00	4646.45	1.00	196.12	3203.35	1.46	103.80	2862.70	1.89	60.43	2048.93	1.94	48.09	1.39
p1	326.48	0.99	53.27	4655.00	1.00	182.71	3621.53	1.65	81.53	2743.93	1.81	66.65	2010.20	1.90	56.75	1.41
p2	324.65	0.98	63.98	4645.15	1.00	231.24	3581.62	1.63	83.08	2631.03	1.73	65.27	1821.15	1.72	53.02	1.37
TILE_1	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.88	0.99	91.50	4681.70	1.01	174.48	3543.25	1.61	85.30	2679.28	1.76	75.88	1951.35	1.84	59.96	1.39
p1	323.32	0.98	103.25	4678.40	1.01	165.31	3234.75	1.47	103.98	2259.03	1.49	86.95	1660.97	1.57	71.20	1.28
p2	325.65	0.99	116.50	4649.40	1.00	196.91	3478.80	1.58	88.86	2425.47	1.60	75.79	1724.20	1.63	58.59	1.32
TILE_2	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.48	0.99	53.20	4663.23	1.00	170.77	3695.12	1.68	78.30	2739.18	1.80	66.01	2081.47	1.97	52.81	1.43
p1	327.80	0.99	53.20	4664.12	1.00	167.50	3778.10	1.72	74.12	2738.75	1.80	59.33	1944.67	1.84	46.44	1.42
p2	329.18	1.00	54.50	4583.30	0.99	258.46	3637.75	1.65	80.72	2709.80	1.78	67.36	1960.22	1.85	52.20	1.40
TILE_3	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.00	0.98	118.38	4666.82	1.01	163.72	3529.03	1.60	85.15	2657.68	1.75	69.70	1960.25	1.85	52.38	1.39
p1	331.45	1.00	139.47	4671.85	1.01	174.43	3423.18	1.56	90.47	2572.50	1.69	67.52	1870.47	1.77	50.12	1.36
p2	330.90	1.00	152.75	4636.77	1.00	195.99	3372.47	1.53	93.93	2503.30	1.65	78.43	1951.95	1.84	60.18	1.36
TILE_4	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.05	0.98	71.15	4666.55	1.01	161.60	3692.65	1.68	78.13	2666.72	1.76	62.98	1997.03	1.89	50.49	1.41
p1	332.02	1.01	79.50	4655.40	1.00	171.50	3690.40	1.68	77.83	2774.10	1.83	64.16	2003.08	1.89	50.06	1.42
p2	327.77	0.99	75.75	4602.43	0.99	222.67	3617.90	1.65	81.22	2624.18	1.73	64.89	1965.62	1.86	52.08	1.39
TILE_5	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	329.77	1.00	83.15	4672.73	1.01	165.08	3619.32	1.65	81.22	2622.32	1.73	65.15	2001.10	1.89	50.67	1.40
p1	330.38	1.00	95.50	4654.65	1.00	172.52	3547.05	1.61	85.48	2515.03	1.66	77.79	1974.88	1.87	58.85	1.38
p2	324.88	0.98	106.75	4631.00	1.00	217.19	3405.85	1.55	92.48	2489.50	1.64	72.26	1804.03	1.71	54.54	1.34
TILE_6	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM

p0	328.15	0.99	59.75	4671.48	1.01	164.02	3603.40	1.64	82.39	2693.60	1.77	68.08	2098.22	1.98	51.91	1.42
p1	327.07	0.99	62.75	4656.30	1.00	191.13	3486.72	1.59	89.16	2488.10	1.64	72.90	1915.53	1.81	55.33	1.36
p2	328.43	0.99	64.00	4662.32	1.00	183.15	3515.50	1.60	87.03	2525.57	1.66	70.72	1832.65	1.73	52.57	1.36
TILE_7	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.07	0.99	137.75	4697.93	1.01	162.09	3530.22	1.61	85.71	2652.75	1.75	70.37	1995.90	1.89	57.42	1.40
p1	326.00	0.99	273.75	4643.10	1.00	203.55	3678.22	1.67	78.78	2570.45	1.69	67.62	1838.83	1.74	51.60	1.37
p2	324.82	0.98	424.48	4669.70	1.01	182.61	3281.72	1.49	98.53	2518.12	1.66	77.84	1820.20	1.72	60.43	1.33
TILE_8	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	330.23	1.00	58.55	4667.05	1.01	162.49	3236.80	1.47	82.90	2547.45	1.68	69.29	1896.20	1.79	56.13	1.35
p1	325.35	0.99	53.52	4664.10	1.00	192.50	3185.70	1.45	86.03	2562.07	1.69	69.06	1819.03	1.72	53.87	1.33
p2	326.05	0.99	61.60	4664.98	1.01	182.28	3218.10	1.46	83.28	2756.70	1.82	71.60	2039.83	1.93	55.21	1.38
TILE_9	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	325.90	0.99	88.53	4691.12	1.01	171.79	3584.62	1.63	82.93	2600.10	1.71	66.18	1976.30	1.87	45.68	1.39
p1	329.20	1.00	100.00	4674.48	1.01	181.03	3312.57	1.51	98.46	2437.68	1.61	83.51	1789.70	1.69	64.51	1.33
p2	322.05	0.98	111.00	4563.10	0.98	275.87	3447.18	1.57	89.73	2587.12	1.70	73.73	2089.82	1.98	53.06	1.38
TILE_10	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.82	0.99	63.48	4646.18	1.00	197.85	3511.82	1.60	87.09	2508.72	1.65	71.15	1806.33	1.71	53.76	1.35
p1	326.45	0.99	73.00	4587.70	0.99	291.37	3430.30	1.56	91.50	2544.62	1.68	76.53	1969.47	1.86	59.39	1.37
p2	327.57	0.99	74.00	4588.07	0.99	266.93	3452.78	1.57	90.77	2543.70	1.68	76.84	1839.80	1.74	59.45	1.35
TILE_11	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	322.15	0.98	89.55	4677.35	1.01	165.99	3510.62	1.60	86.81	2688.30	1.77	69.05	1893.20	1.79	55.98	1.38
p1	325.15	0.98	104.00	4675.57	1.01	185.93	3261.00	1.48	101.93	2269.22	1.49	87.23	1705.28	1.61	68.03	1.29
p2	324.93	0.98	109.25	4637.23	1.00	205.41	3428.68	1.56	91.12	2638.82	1.74	71.00	1830.03	1.73	59.56	1.36
TILE_12	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.38	0.99	64.00	4686.02	1.01	168.00	3824.88	1.74	72.55	2756.75	1.82	64.94	2080.80	1.97	52.85	1.44
p1	326.20	0.99	63.45	4653.85	1.00	178.92	3599.15	1.64	83.62	2542.12	1.67	70.54	1768.08	1.67	56.44	1.35
p2	326.62	0.99	64.00	4676.02	1.01	177.02	3599.00	1.64	82.48	2645.30	1.74	70.97	1884.15	1.78	56.56	1.38
TILE_13	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	324.32	0.98	98.00	4654.88	1.00	184.01	3562.65	1.62	84.51	2578.30	1.70	67.48	1895.33	1.79	55.75	1.37
p1	326.07	0.99	114.00	4679.10	1.01	177.84	3641.30	1.66	80.45	2732.80	1.80	60.25	1831.15	1.73	52.28	1.39
p2	324.32	0.98	120.90	4631.98	1.00	210.29	3310.47	1.51	98.56	2524.70	1.66	85.34	1821.85	1.72	67.73	1.33
TILE_14	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	327.57	0.99	65.50	4676.93	1.01	171.09	3594.88	1.63	81.96	2722.70	1.79	60.55	1971.65	1.86	45.68	1.40
p1	324.95	0.98	64.00	4644.73	1.00	184.16	3482.82	1.58	88.06	2646.18	1.74	70.74	1927.33	1.82	54.65	1.38
p2	317.38	0.96	73.90	4648.70	1.00	203.77	3487.07	1.59	87.44	2646.93	1.74	70.29	2028.17	1.92	55.80	1.39
TILE_15	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.57	0.99	98.75	4662.65	1.00	175.08	3238.65	1.47	83.19	2551.68	1.68	68.98	1821.33	1.72	53.23	1.34
p1	325.00	0.98	105.50	4668.45	1.01	170.00	3229.22	1.47	83.63	2784.18	1.83	70.99	2033.55	1.92	56.10	1.39
p2	331.05	1.00	118.25	4644.50	1.00	220.59	3059.28	1.39	94.62	2349.43	1.55	81.45	1740.50	1.65	66.33	1.29
TILE_16	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	328.00	0.99	68.75	4670.00	1.01	174.00	3440.00	1.57	88.40	2561.00	1.60	75.64	1841.17	1.74	58.26	1.36

p0	328.00	0.99	68.78	4670.98	1.01	174.29	3449.60	1.57	90.40	2561.95	1.69	75.64	1841.17	1.74	59.26	1.36
p1	325.70	0.99	71.42	4677.23	1.01	172.45	3401.70	1.55	93.67	2460.28	1.62	81.65	1846.60	1.75	66.63	1.34
p2	322.95	0.98	74.00	4639.82	1.00	195.75	3397.47	1.54	93.80	2394.03	1.58	78.35	1678.92	1.59	61.76	1.30
TILE_17	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	Actual	Ratio	QoS	GM
p0	326.57	0.99	144.97	4676.32	1.01	162.43	3549.47	1.61	86.15	2554.18	1.68	75.73	1964.75	1.86	59.28	1.38
p1	325.15	0.98	188.40	4666.27	1.01	178.36	3183.65	1.45	109.44	2316.95	1.53	91.94	1656.70	1.57	72.06	1.28
p2	319.32	0.97	237.50	4619.10	1.00	231.36	3550.60	1.61	85.87	2417.75	1.59	76.28	1747.60	1.65	57.30	1.33
p0_score:	24.98															
p1_score:	24.44															
p2_score:	24.36															

Infrastructure_Operations_Scores:		vmotion	svmotion	deploy
Completed_Ops_PerHour		16.50	11.00	5.50
Avg_Seconds_To_Complete		35.75	23.62	342.66
Failures		0.00	0.00	0.00
Ratio		1.03	1.22	1.38
Number_Of_Threads		1	1	1
Summary		Run_Is_Compliant		Turbo_Setting:0
		Number_Of_Compliance_Issues(0)*		Median_Phase(p1)
Unreviewed_VMmark2_Applications_Score		24.44		
Unreviewed_VMmark2_Infrastructure_Score		1.20		
Unreviewed_VMmark2_Score		19.79		

Configuration

Virtualization Software	
Hypervisor Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware ESX 4.1.0 U3 Build 800380 / 08-30-2012
Datacenter Management Software Vendor, Product, Version, and Build / Availability Date (MM-DD-YYYY)	VMware vCenter Server 5.1.0 Build 799731 / 09-10-2012
Supplemental Software	None
Servers	
Quantity	2
Server Manufacturer and Model	Dell PowerEdge R820
Processor Vendor and Model	Intel E5-4650
Processor Speed (GHz)	2.70
Total Sockets/Total Cores/Total Threads	4 Sockets / 32 Cores / 64 Threads
Primary Cache	32 KB I + 32 KB D on chip per core
Secondary Cache	256 KB I+D on chip per core
Other Cache	70 MB I+D on chip per chip

Array Cache	20 MB L3 on chip per chip
BIOS Version	1.5.0
Memory Size (in GB, Number of DIMMs)	512 GB, 32 x 16 GB
Memory Type and Speed	2Rx4 PC3-12800R-11 ECC / 1600 MHz
Disk Subsystem Type	FC SAN
Number of Disk Controllers	1
Disk Controller Vendors and Models	Dell PERC H710
Number of Host Bus Adapters	2
Host Bus Adapter Vendors and Models	QLogic 2562 Dual-Port 8Gb Fibre Channel HBA
Number of Network Controllers	2
Network Controller Vendors and Models	Integrated Intel I350 Quad-Port 1-GbE Adapter, 1 x Intel 82599EB 10-GbE SFI/SFP+ Network Adapter
Other Hardware	None
Other Software	None
Hardware Availability Date (MM-DD-YYYY)	03-06-2012
Software Availability Date (MM-DD-YYYY)	03-26-2013
Network	
Network Switch Vendors and Models	1 x Dell PowerConnect 6248
Network Speed	10Gbps for Olio and DS2, 1Gbps for rest
Storage	
Array Vendors, Models, and Firmware Versions	2 x Fusion-io ION Data Accelerator, FW 2.0.1
Fibre Channel Switch Vendors and Models	Brocade 300
Disk Space Used	15038.8 GB
Array Cache Size	N/A
Total Number of Physical Disks Used	8 x HDDs, 6 x PCI-e Flash
Total Number of Enclosures/Pods/Shelves Used	2
Number of Physical Disks Used per Enclosure/Pod/Shelf	2 HDDs for OS 3 PCI-e Flash
Total Number of Storage Groups Used	0
Number of LUNs Used	12
LUN Size and Number of Disks Per LUN	All LUNs striped across 3 PCI-e Flash cards • 1 LUN at 1200GB (even DS2DBs) • 1 LUN at 600GB (odd DS2DBs) • 1 LUN at 800GB (even DS2Webs) • 1 LUN at 400GB (odd DS2Webs) • 1 LUN at 2100GB (even mailservers) • 1 LUN at 1100GB (odd mailservers) • 1 LUN at 400GB (even OlioDBs)

	• 1 LUN at 200GB (odd OlioDBs) • 1 LUN at 2000GB (even OlioWebs) • 1 LUN at 1000GB (odd OlioWebs) • 1 LUN at 200GB (standbys and DeployTemplate) • 1 LUN at 100GB (sVMotion and Deploy Target LUN)
RAID Type	SUT OS: RAID1 ION OS: RAID1 ION Flash: RAID0
Number of Members per RAID Set	SUT OS:2 ION OS: 2 ION Flash: 3
Disk Vendors, Models, and Speeds	8 x Dell 146GB 15K RPM SAS 6 x Fusion-io 2.4 TB ioDrive2 Duo
Datacenter Management Server	
System Model	Dell PowerEdge 1950
Processor Vendor and Model	Intel Xeon E5450
Processor Speed (GHz)	3.00
Total Sockets/Total Cores/Total Threads	2 Sockets / 4 Cores / 4 Threads
Memory	16 GB
Network Controller(s) Vendors and Models	Integrated Broadcom BCM5708C NetXtreme II GigE
Operating System, Version, Bitness, and Service Pack	Microsoft Windows Server 2008 R2 Enterprise (64-bit)
Other Hardware	None
Other Software	None
Clients	
Total Number of Clients / Total Physical Clients / Total Virtual Client Hosts	7 (1 Dedicated Prime client, 6 Physical ESX servers)
System Model(s)	Dell PowerEdge R410
Processor Vendor(s) and Model(s)	Intel Xeon E5620
Processor Speed(s) (GHz)	2.40
Total Sockets/Total Cores/Total Threads	2 Sockets / 24 Cores / 24 Threads
Memory per Physical Client	Prime Client: 4 GB Clients 0-5: 24 GB
Network Controller(s) Vendors and Models	Prime Client: Intel PRO/1000 PT Dual Port Server Adapter Clients 0-3: 1 x Integrated Broadcom BCM5716 NetXtreme II GbE
Operating System, Version, Bitness, and Service Pack	Prime Client: Microsoft Windows Server 2003 Enterprise 32-bit, Service Pack 2 Physical Clients: VMware ESX 4.1.0 (Build 260247) Virtual Clients: Microsoft Windows Server 2008 R2 Enterprise 64-bit
Number of Virtual Clients	18
Number of vCPUs Per Virtual Client	4
Number of vMem (GB) Per Virtual Client	4
Virtual Client Networking Notes	1 vSwitch for Service Console, 1 vSwitch for virtual clients
Virtual Client Storage Notes	virtual client VMs used local storage. 1 x 160GB 7.2 RPM SATA

Other Hardware	None
Other Software	None

Notes for Workload

Virtualization Software Notes

- All VMs used virtual hardware V7
- Ethernet adapter type set to VMXNET3 for all VMs (default VMXNET2)
- Logging was disabled for all VMs (default enabled)
- Floppy and CDROM removed for all VMs (default enabled)
- Firewall disabled for Console OS (default enabled)
- All VMs: Paravirtual Controller
- Cluster DRS Automation Level set to "Fully Automated", Level 1
- Logical CPU layout changed for all VMs (except Standby and Mailserver) to one socket with multiple cores (default: multiple sockets with one core per socket)

Advanced Settings:

- Cpu.CoschedCrossCall=0 (default 1)
- Cpu.CreditAgePeriod=500 (default 1)
- Cpu.HaltingMsecPenalty=0 (default 800)
- DataMover.HardwareAcceleratedInit=0 (default 1)
- DataMover.HardwareAcceleratedMove=0 (default 1)
- Disk.SchedNumReqOutstanding=256 (default 32)
- Irq.BestVcpuRouting=1 (default 0)
- Irq.RoutingPolicy=0 (default 2)
- Mem.BalancePeriod=0 (default 15)
- Mem.SamplePeriod=0 (default 60)
- Mem.ShareScanGHz=0 (default 4)
- Misc.TimerMaxHardPeriod=4000 (default 100000)
- Misc.TimerMinHardPeriod=2000 (default 100)
- Misc.WorldletHTSharing=45 (default 90)
- Net.AllowPT=1 (default 0)
- Net.MaxNetifRxQueueLen=500 (default 100)
- Net.MaxNetifTxQueueLen=1000 (default 500)
- Net.NetTxCompletionWorldlet=0 (default 1)
- Net.NetTxWorldlet=0 (default 2)
- Numa.AutoSplitVM=0 (default 1)
- Numa.LTermFairnessInterval=0 (default 5)
- Numa.PageMigEnable=0 (default 1)
- Numa.MonMigEnable=0 (default 1)
- Numa.PreferHT=1 (default 0)
- Numa.RebalancePeriod=60000 (default 2000)
- Numa.SwapInterval=1 (default 2)
- Numa.SwapLoadEnable=0 (default 1)
- Numa.SwapLocalityEnable=0 (default 1)
- VMFS3.HardwareAcceleratedLocking=0 (default 1)

Driver Options:

- /vmkernel/module/qla2xxx.o/options= "ql2xintrdelaytimer=10" (default 0)
- /vmkernel/module/ixgbe.o/options= "InterruptThrottleRate=2000,2000 VMDQ=16,16" (default 16000, 8)

Server Notes

Server BIOS Settings:

- Intel Turbo Boost Technology up to 3.80 GHz (default)
- System Profile set to Performance in BIOS (default)
- Hardware Prefetcher set to Disabled (default Enabled)
- Adjacent Cache Line Prefetcher set to Disabled (default Enabled)

Networking Notes

vSwitch Configuration:

- vSwitch0 for Service Console on vmnic0 at 1 Gb/s
- vSwitch1 for Mailserver VMs on vmnic1 at 1 Gb/s
- vSwitch2 for Deploy and Standby VMs on vmnic2 at 1 Gb/s
- vSwitch3 for vMotion vmnic3 at 1 Gb/s
- vSwitch4 for Olio VMs on vmnic4 at 10 Gb/s
- vSwitch5 for DS2 VMs on vmnic5 at 10 Gb/s

Storage Notes

- Each Dell PowerEdge R720 configured with 3 x 2.4TB Fusion-io ioDrive2 Duo PCI-e Flash cards and Fusion-io ION Data Accelerator software
- Configuration for each Fusion-io ION Data Accelerator:
 - Dell PowerEdge R720
 - 2 x Intel Xeon E5-2690 2.90 GHz
 - 256 GB (16 x 16 GB, 2Rx4 PC3-12800R-11 ECC / 1600 MHz)
 - 2 x QLogic 2562 Dual-Port 8Gb Fibre Channel HBA
 - 2 x 146 GB 15K RPM HDD, RAID 1
 - 3 x 2.4TB Fusion-io ioDrive2 Duo PCI-e Flash Cards, RAID 0
- VM Layout
 - ION Data Accelerator 1
 - 1 LUN at 1200GB (even DS2DB)
 - 1 LUN at 800GB (even DS2Web)
 - 1 LUN at 2100GB (even Mailserver)
 - 1 LUN at 400GB (even OlioDB)
 - 1 LUN at 2000GB (even OlioWeb)
 - 1 LUN at 200GB (Standby and DeployTemplate)
 - ION Data Accelerator 2
 - 1 LUN at 600GB (odd DS2DB)
 - 1 LUN at 400GB (odd DS2Web)
 - 1 LUN at 1100GB (odd Mailserver)
 - 1 LUN at 200GB (odd OlioDB)
 - 1 LUN at 1000GB (odd OlioWeb)
 - 1 LUN at 100GB (Deploy and SVMotion target)
 - All LUNs were configured as block devices and no system memory was used for write caching

Datacenter Management Server Notes

None

Operating System Notes

- All MailServer VMs running Microsoft Windows Server 2008 R2 Enterprise (64-bit)
- All Standby VMs running Microsoft Windows Server 2003 R2 Enterprise SP2 (32-bit)
- All SLES11 VMs were updated with SP2

Software Notes

- Each Mailserver VM running Microsoft Exchange Server 2007 Enterprise SP3 (64-bit)

Client Notes

- Prime Client split from Client0 and run on a non-virtualized copy of Microsoft Windows Server 2003 Enterprise SP2 (32-bit)
- Prime Client was running VMware vSphere PowerCLI-4.1.1-332441
- All clients were run on virtual machines that were each defined with 4 vCPUs, 4GB memory, 1 VMXNET3 network and 32GB disk space.
- Each client virtual machine was running Microsoft Windows Server 2008 R2 Enterprise (64-bit)
- 6 physical clients ran 3 virtual clients each
- All physical clients were installed with VMware ESX 4.1.0 (Build 260247)

Other Notes

None

This is a full disclosure report for a VMmark benchmark result. All published VMmark results must be from fully-compliant tests for which a full disclosure report is publicly available.

For information about VMmark and the rules regarding its usage visit www.vmware.com/products/vmmark.

VMware and VMmark are trademarks or registered trademarks of VMware, Inc. VMware® VMmark® is a product of [VMware, Inc.](http://www.vmware.com) VMmark utilizes the SPEC Power and Temperature Daemon (SPEC PTDaemon), which is available from the Standard Performance Evaluation Corporation (SPEC®). VMmark results are not SPEC metrics and cannot be compared to SPEC metrics in any way.