

---

# Dell OpenManage Essentials MIB Import

## Monitoring HP Servers and Third-Party Hardware

---

OME Engineering



This document is for informational purposes only and may contain typographical errors and technical inaccuracies. The content is provided as is, without express or implied warranties of any kind.

© 2016 Dell Inc. All rights reserved. Dell and its affiliates cannot be responsible for errors or omissions in typography or photography. Dell, the Dell logo, OpenManage, PowerVault, PowerConnect, Dell EqualLogic, and PowerEdge are trademarks of Dell Inc. Microsoft, Windows, and Windows Server are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others.

July 2016 | Rev 1.0

## Contents

Introduction.....	5
Scope .....	5
About Importing Traps.....	5
Prerequisites .....	6
Using MIB Import Functionality .....	7
Import MIB .....	8
Remove MIB.....	13
Custom Trap Definitions .....	14
Alert Categories & Definitions .....	18
Reset Built-in trap definitions .....	21
Imported HP Server traps in Essentials.....	22
Import View Components.....	23
Severity Configuration By Value.....	26
Parsing MIBs having Novel NMS Comments.....	30
HP Server MIB Module definition and reference MIBs .....	31
Learn More .....	31

## Tables

Table 1.	Benefits of trap definitions in Essentials .....	5
----------	--	---

## Figures

Figure 1.	Manage MIBs View .....	7
Figure 2.	Selecting a MIB for parsing .....	8
Figure 3.	HP Server MIB Dependencies .....	8
Figure 4.	Parsed HP Server MIB Trap Definitions .....	10
Figure 5.	HP Server MIB Trap Definition.....	10
Figure 6.	HP Server MIB Parsed Trap Definition.....	11
Figure 7.	Remove MIB View .....	14
Figure 8.	Unknown Trap received in OME from HP CPQIDA-MIB.....	15
Figure 9.	Unknown Traps - Custom Trap Definition View .....	16
Figure 10.	Custom trap definition add view .....	17
Figure 11.	Trap Filter View .....	17
Figure 12.	Delete Trap View.....	18
Figure 13.	Alert Category view.....	19
Figure 14.	Edit Trap view .....	20
Figure 15.	Reset Trap view .....	21
Figure 16.	Import View .....	23
Figure 17.	Traps Grid .....	25
Figure 18.	Grid Column Filters .....	26
Figure 19.	SNMP trap definition example showing trap variable based Severity.....	27
Figure 20.	Severity Configuration By Value Dialog Box - Trap Variables .....	28
Figure 21.	Severity Configuration By Value Dialog Box - Severity Selection .....	29
Figure 22.	Trap Definition having NMS comments .....	30
Figure 23.	HP Server MIB.....	31

## Introduction

Dell OpenManage Essentials (OME) is a hardware management application that provides a comprehensive view of Dell systems, devices, and components in the enterprise's network. Health monitoring in OME has two parts to it:

- SNMP traps received from the remote device.
- Health poll to retrieve the latest status of the remote device.

The *Dell OpenManage Essentials MIB Import* option allows you to extract trap definitions from SNMP supported device MIB files. The extracted traps can be viewed and edited before they are imported. The imported trap definitions help OME to properly classify the incoming traps. To know more about the benefits of importing trap definitions, see [About Importing Traps](#).

**Note:** From OpenManage Essentials version 2.2 onwards, the MIB Import functionality is integrated within the OpenManage Essentials user interface.

## Scope

This document provides an overview of the *OME MIB Import* functionality and the benefits of importing trap definitions in OME.

## About Importing Traps

If you want to monitor (classify incoming SNMP traps) an SNMP supported device that is not currently supported by OME, use the *MIB Import* option to import that device's SNMP trap definitions.

Ensure the following before using the *MIB Import* option:

- The remote device supports SNMP v1 or v2 protocol
- SNMP services on the remote device are working as expected and the trap destination points to OME system
- You have the device-specific SNMP MIB files (main MIB and its reference MIBs)
- Validate the device-specific MIBs by using a standard MIB compiler tool

The following table provides a comparison of the traps both before and after the definitions are imported to the OME database.

**Table 1.** Benefits of importing trap definitions in OME

Feature	Before Importing the Trap	After Importing the Trap
Can I see traps coming from the device in the OpenManage Essentials Alerts portal?	Yes	Yes
Will traps have a severity value?	No, the severity is unknown.	Yes
Will traps have a valid name?	No, the name is unknown.	Yes, the trap name is defined in the MIB

Will traps have a valid event category name?	No, the event category name is unknown.	Yes, a new category is created by default.
Will the traps have a description?	Yes, all the description details are present. However, the details are not formatted	Yes, the description is formatted according to the trap definition
Will the traps display the trap variable values?	Yes	Yes
Will the traps display the Enterprise OID, Specific OID, and Generic OID?	Yes	Yes
Will the traps display additional trap variables which can be used for debugging?	Yes, however, the details are not formatted.	Yes
Will the traps display the host name or IP address of the device?	Yes	Yes
Can I use the traps in various alert actions to forward the trap to another management console, execute a task, or filter the unwanted traps?	Yes, but the features are limited. Rules specific to severity, event category, event name, and so on are not possible	Yes, the traps are defined so all the alert actions are supported based on the trap name, category, severity, and so on
Can I perform various UI actions (such as acknowledge, delete and so on) on the traps?	Yes	Yes
Will purging of alerts work on the traps?	Yes	Yes

**Note:**

- The MIB Import option will not accurately determine the severity from the MIB. You will need to add severity context to each trap.

## Prerequisites


The *MIB Import* functionality is included within OME version 2.2 and later.

## Using MIB Import Functionality

The Import MIB functionality is available in the alert management section. The **Manage MIBs** view has the following options that are accessible in the left panel:

- **Import MIB** – This option allows you to:
  - Select a MIB file to import
  - Parse the selected MIB
  - View or update the extracted trap definitions of the MIB
  - Import the trap definitions to OME
- **Remove MIB** – This option allows you to:
  - View the imported MIBs
  - Remove those MIBs (traps definitions) from OME

Figure 1. Manage MIBs View



## Import MIB

To import the trap definition of a device, browse and select the SNMP supported device MIB that has the required trap definitions. For example, if you want to import the trap definitions of a HP server to OME, select the **CPQIDA-MIB.mib** (Module name: CPQIDA-MIB, Intelligent Drive Array Management SNMP MIB) file.

### Note:

This white paper refers to some of the HP ProLiant server MIBs. You can also refer to <http://h18013.www1.hp.com/products/servers/management/hpsim/mibkit.html> for information on HP servers MIBs. The examples included in this white paper refer to certain HP MIBs (CPQSINFO-MIB, CPQHLTH-MIB, CPQHOST-MIB, and CPQNIC-MIB).

You can select \*.mib, \*.txt and \*.my files. If you have a MIB file with any other file name extension, you can rename the file to .mib, .txt, or .my and then select it.

Figure 2. Selecting a MIB for parsing

The screenshot shows a web interface titled "Import MIB". Below the title is a instruction: "Select a MIB file to parse and import its trap details." A file selection dialog is open, titled "Select files for upload". It contains a table with one row: "CPQIDA-MIB.mib" with a size of "654.54 KB". Below this table is a summary row: "Total" with "100%" and "654.54 KB". At the bottom of the dialog are "Cancel" and "Browse" buttons. Below the dialog, there is a "Select a MIB File:" label, a dropdown menu showing "CPQIDA-MIB.mib", and a "Parse MIB" button.


When you parse the earlier mentioned HP server MIB for the first time, it will display the message shown in Figure 3, prompting you to add the required reference MIBs to the MIB repository. OME bundles various standard reference MIBs which help parsing any MIB which refers to them. In this example, only one MIB file is listed in the message because the rest of the required MIBs are already part of the MIB repository. To parse the specific HP MIB, ensure you have added the required reference MIBs to the MIB repository. In this example, it is **CPQ\_HOST\_M14.mib** (Module name: CPQHOST-MIB) Host Operating System Information MIB. For information on adding MIBs to the MIB repository, see [MIB Repository](#).

For information on the HP server MIB dependency, see [HP Server MIB Module definition and reference MIBs](#).

Figure 3. HP Server MIB Dependencies



## Monitoring HP Servers and Third Party Hardware



While browsing for the MIB, select referred MIB along with required MIB to parse and store in OME, and then parse the required MIB. OME will parse the MIB and populate the grid with the parsed trap definitions and add the reference MIB in the repository. The number of traps that were parsed is displayed below the grid. The following figure shows the parsed CPQIDA-MIB.mib file.

Figure 4. Parsed HP Server MIB Trap Definitions

Import MIB

Select a MIB file to parse and import its trap details.

Select files for upload

CPQIDA-MIB.mib 654.54 KB

Total 100% 654.54 KB

Cancel Browse

Select a MIB File: CPQIDA-MIB.mib Parse MIB

Event Details

Category Name: CPQIDA-MIB ☐ Apply the selected event category to all traps

Severity: Normal ☐ Apply the selected severity to all traps

Traps Available for Import

Drag a column header and drop it here to group by that column

Name	Category Name	Severity	Format String	Enterprise OID	Description	Generic Trap ID	Specific Trap ID
cpqSDCardDeviceFailure	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	SD card device has detected a failure.	6	1
cpqBatteryFailure	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	Battery has detected a failure.	6	1704
cpqBatteryWarning	CPQIDA-MIB	Warning	\$3	.1.3.6.1.4.1.674.0.1	Battery has detected a warning.	6	1703
cpqBatteryNormal	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Battery has returned to normal.	6	1702
cpqDeviceConfigError	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	Device configuration error detected.	6	1653
cpqDeviceRemove	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Device removed from system.	6	1652
cpqDeviceAdd	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Device added to system.	6	1651
cpqProcessorDeviceStatusFailure	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	Processor device status has detected a failure.	6	1604
cpqProcessorDeviceStatusWarning	CPQIDA-MIB	Warning	\$3	.1.3.6.1.4.1.674.0.1	Processor device status has detected a warning.	6	1603
cpqProcessorDeviceStatusNormal	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Processor device status has returned to normal.	6	1602
cpqLogFull	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	Log size is at capacity.	6	1554
cpqLogWarning	CPQIDA-MIB	Warning	\$3	.1.3.6.1.4.1.674.0.1	Log size is near capacity.	6	1553
cpqLogNormal	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Log size is no longer near or at capacity.	6	1552

Reset All Import Traps

Number of traps parsed: 52 from MIB file "CPQIDA-MIB.mib"

The following figure shows the first trap defined in the CPQIDA-MIB.mib file.

Figure 5. HP Server MIB Trap Definition

```

cpqSDCardDeviceFailure                                TRAP-TYPE
    ENTERPRISE baseboardGroup
    VARIABLES { cpqSystem,
                cpqTableIndexOID,
                cpqMessage,
                cpqCurrentStatus,
                cpqPreviousStatus,
                cpqData }
    DESCRIPTION
        "SD card device has detected a failure."

    --HP trap annotation
    --#TYPE      "Server SD Card Device Failure"
    --#SUMMARY    "%s"
    --#ARGUMENTS {2}
    --#SEVERITY   CRITICAL
    --#TIMEINDEX  99
    --#STATE      DEGRADED

    ::= 1

```

For the earlier trap definition, the information extracted in OME is shown in Figure 6. Some information is added to the MIB definition which is required for proper classification. For example, the MIB module name will be the new event category and the trap severity is critical. If necessary, you can change both these values.

Figure 6.HP Server MIB Parsed Trap Definition

Traps Available for Import								
Drag a column header and drop it here to group by that column								
Name	Category Name	Severity	Format String	Enterprise OID	Description	Generic Trap ID	Specific Trap ID	
cpqSDCardDeviceFailure	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	SD card device has detected a failure.	6	1	

Traps Available for Import								
Drag a column header and drop it here to group by that column								
Name	Category Name	Severity	Format String	Enterprise OID	Description	Generic Trap ID	Specific Trap ID	
<input checked="" type="checkbox"/> cpqSDCardDeviceFailure	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	SD card device has detected a failure.	6	1	
<input type="checkbox"/> cpqBatteryFailure	CPQIDA-MIB	Unknown	\$3	.1.3.6.1.4.1.674.0.1	Battery has detected a failure.	6	1704	
<input type="checkbox"/> cpqBatteryWarning	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Battery has detected a warning.	6	1703	
<input type="checkbox"/> cpqBatteryNormal	CPQIDA-MIB	Normal	\$3	.1.3.6.1.4.1.674.0.1	Battery has returned to normal.	6	1702	
<input type="checkbox"/> cpqDeviceConfigError	CPQIDA-MIB	Warning	\$3	.1.3.6.1.4.1.674.0.1	Device configuration error detected.	6	1653	
<input type="checkbox"/> cpqDeviceRemove	CPQIDA-MIB	By VarBind Value	\$3	.1.3.6.1.4.1.674.0.1	Device removed from system.	6	1652	
<input type="checkbox"/> cpqDeviceAdd	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Device added to system.	6	1651	

You can change the event category, severity and format string of these parsed traps before importing them. For more information about editing the default values, see [Import View Components](#). Notice that this specific trap severity can also be selected as “By VarBind Value” because the “cpqSDCardDeviceFailure” variable is enumeration based. The following figures show the possible values in the MIB and the Severity Configuration window in OME.

cpqSDCardDeviceFailure

TRAP-TYPE

ENTERPRISE baseboardGroup

VARIABLES { cpqSystem,

cpqTableIndexOID,

cpqMessage,

cpqCurrentStatus,

cpqPreviousStatus,

cpqData }

DESCRIPTION

Severity Configuration by Value : cpqSDCardDeviceFailure

Severity Configuration by Value

Select the Variable: \$4

Drag a column header and drop it here to group by that column

Trap Variable	Severity	Object ID	Object Value
\$4	Normal	1	other
\$4	Unknown	2	unknown
\$4	Normal	3	ok
\$4	Critical	4	nonCritical
\$4	Critical	5	critical
\$4	Normal	6	nonRecoverable
\$5	Normal	1	other
\$5	Unknown	2	unknown
\$5	Normal	3	ok
\$5	Critical	4	nonCritical
\$5	Critical	5	critical
\$5	Normal	6	nonRecoverable

OK
Reset
Cancel

After performing the required updates, click **Import Traps**.

**Note:**

- Multiple selections are allowed in the grid and the check boxes allow you to change the category name and severity of multiple selected trap records at a time. You can also modify the individual rows based on your preference.
- Ensure that you have not selected the event category or severity check boxes if you do not want to override the changes done in the grid for these two columns. If you want to import with the changes (Event Category and Severity) performed in the grid, then select these check boxes.


**Important:**

1. In the earlier figure, OME is able to parse the NMS comments and calculate the recommended severity. If you want to take these severities values available in the grid, then deselect the **Apply the selected severity to all traps** check box.
  2. If you do not want to take the NMS-based severity, you can select the **By Varbind Value** based severity for those specific traps. For an example, see Figure 6.
  3. The Format String field does not contain the desirable values, therefore %d must be replaced with \$1 for these trap definitions.
- Reimport the same MIB: If you want to import trap definitions from a newer version of a previously imported MIB, this option allows you to do so. You need not remove that MIB.
  - Reimport only updates to the previously imported trap definitions. It does not remove the extra trap definitions which may not be part of the newer version of the MIB file.

## Remove MIB

After you have imported the trap definitions from the CPQIDA-MIB.mib file to OME, the MIB file is listed in the **Imported MIB** list of the **Remove MIB** view. If you no longer want these chassis trap definitions in OME, you can remove them. To remove the trap definitions, select the appropriate MIB files from the list and click **Remove MIB**.

Figure 7.Remove MIB View



**Note:**

- If necessary, you can select multiple MIBs for removal.
- After you remove the trap definitions, all the associated alert actions, filters, and views for the traps will not work. For more details, see [About Importing Traps](#).
- All classified and received traps (from this specific SNMP device and traps related to this MIB) in OME will be deleted. Before you remove the MIB, ensure you have acknowledged or resolved all the problems reported in the OME events console for this device or component.

## Custom Trap Definitions


You can use the Add Trap view to search for unknown traps received in OME and manually define trap definitions and import them to OME. For example, you may want to manually define trap definitions in the following scenarios:

- When you may not want to import the entire MIB file
- The MIB file for the device which is sending traps to OME is not available
- The MIB file cannot be compiled due to formatting issues

Monitoring HP Servers and Third Party Hardware

The following figure shows the cpqDaLogDrvStatusChange trap from CPQIDA-MIB received in OME which is categorized as unknown (CQPIDA-MIB has not been imported to OME using Import MIB view).


Figure 8.Unknown Trap Received in OME From HP CPQIDA-MIB



The Add Trap view allows searching for unknown traps that are received in OME, and automatically populates the Enterprise OID, Generic ID, and Specific ID fields for the selected unknown trap. This allows you to add the trap definition manually.

The following figure shows the **Unknown Traps** window which is displayed when you click **View Unknown Traps**.

Figure 9.Unknown Traps - Custom Trap Definition View



After the unknown trap is selected, you can manually define the trap definition in the **Add Trap** view by selecting an existing category or defining a new category, entering details for the Trap Name, Description, Format String, and selecting Severity. Refer to the trap definition in the MIB file to accurately define the trap using Add Trap view.



The following figure shows the manual definition of cpqDaLogDrvStatusChange trap in the **Add Trap** pane and the values in the **Trap(s) Available for Import** grid after you click **Add Trap**. As seen in the figure, a new category is defined instead of selecting an existing category, and the Enterprise OID, Generic ID, and Specific ID fields are automatically populated. After you click **Add Trap**, the trap definitions displayed in the grid are imported and the status of the import is displayed in the status bar.

Figure 10. Custom trap definition add view

**Custom Trap Definitions**

Enter trap details or search for unknown traps that you want to add.

**Add Trap**

Category Name:  Description:

Trap Name:  Generic ID:

Enterprise OID:  Specific ID:

Format String:  Severity:

**Delete User-Defined Traps**

Drag a column header and drop it here to group by that column

Name	Category Name	Severity	Enterprise OID	Description	Format String	Generic Trap ID	Specific Trap ID
customTrap	CPQIDA-MIB	Normal	.1.2.3.4.55	This is custom trap	\$1 format string	6	100
t1	MyCustomCategory	Normal	.1.2.3.4.56	this is trap in custom category	\$1 format	6	1000

The **Delete User-Defined Traps** pane allows you to delete only the user-defined traps that were imported to OME by using the **Add Trap** pane. The **Delete User-Defined Traps** lists all the user-defined traps in the grid. You can filter the traps list in the **Delete User-defined Traps** grid by entering Trap Name, Enterprise OID, and so on by clicking filter icon of grid as shown in Figure 11. The grid allows multiple traps to be selected for deletion as shown in Figure 12. When you click **Delete Trap**, the selected trap definitions in the grid will be deleted from OME after your confirmation. The status bar will display a message indicating successful deletion of the traps from OME.

**Note:**

- After deleting the trap definition, the associated alert actions and already received alerts will also be deleted from OME.
- If the deleted trap definition is the last trap being deleted in the user-defined category, then that specific user-defined category will also be deleted from OME.
- The **Delete User-Defined Trap** pane does not allow the deletion of predefined trap definitions and trap definitions that are imported from MIB files by using **Import MIB** view.

Figure 11. Trap Filter

**Delete User-Defined Traps**

Drag a column header and drop it here to group by that column

Name	Category Name	Severity	Enterprise OID	Description	Format String	Generic Trap ID	Specific Trap ID
t1		mal	.1.2.3.4.56	this is trap in custom category	\$1 format	6	1000

**Filter Dialog:**

Select All

☐ customTrap

☐ t1

Show rows with value that

Starts with:

And:

Contains:

Figure 12. Delete Trap View

Delete User-Defined Traps

Drag a column header and drop it here to group by that column

Name	Category Name	Severity	Enterprise OID	Description	Format String	Generic Trap ID	Specific Trap ID
customTrap	CPQIDA-MIB	Normal	.1.2.3.4.55	This is custom trap	\$1 format string	6	100
<input checked="" type="checkbox"/> t1	MyCustomCategory	Normal	.1.2.3.4.56	this is trap in custom category	\$1 format	6	1000

Delete Trap

## Alert Categories & Definitions

The **Alert Categories & Definitions** view allows you to view all alert categories and edit traps. The **Edit Trap** view allows you to modify the Category Name, Severity, and Format String of the following:

- All traps available in OME (predefined traps)
- Imported traps - Traps imported using the **Import Trap** view
- Manually defined traps - Traps defined using the **Add Trap** view

Figure 13 and Figure 14 show the **Edit Trap** view where you can search for the trap that you want to edit based on Trap Name or Enterprise OID or by using the filter option provided by grid. Alternatively, you can select the traps by selecting a specific event category or trap from the expandable Event Categories tree view on the left.

Figure 13. Alert Category View




Figure 14. Edit Trap View

**Edit Trap for CPQIDA-MIB**

Select the traps that you want to edit. All traps can be edited.

Trap Name or Enterprise OID:

Name	Category Name	Severity	Format String	Enterprise OID	Description	Generic Trap ID	Specific Trap ID
cpqFanEnclosureExtendedRemoval	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Fan enclosure has been removed from system for an extended amount of time.	6	1454
cpqRedundancyNormal	CPQIDA-MIB	Info	\$3	1.3.6.1.4.1.674.0.1	Redundancy has returned to normal.	6	1304
cpqPowerSupplyWarning	CPQIDA-MIB	Warning	\$3	1.3.6.1.4.1.674.0.1	Power supply has detected a warning.	6	1353
cpqPowerSupplyFailure	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Power supply has detected a failure.	6	1354
cpqMemoryDeviceNonRecoverable	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Memory device status is non-recoverable.	6	1405
cpqChassisIntrusionDetected	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Chassis intrusion has been detected.	6	1254
cpqVoltageProbeWarning	CPQIDA-MIB	Warning	\$3	1.3.6.1.4.1.674.0.1	Voltage probe has detected a warning value.	6	1153
cpqMemoryDeviceWarning	CPQIDA-MIB	Warning	\$3	1.3.6.1.4.1.674.0.1	Memory device status is noncritical.	6	1403
cpqTemperatureProbeFailure	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Temperature probe has detected a failure value.	6	1054
cpqChassisIntrusionNormal	CPQIDA-MIB	Info	\$3	1.3.6.1.4.1.674.0.1	Chassis intrusion has returned to normal.	6	1252
cpqLogFull	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Log size is at capacity.	6	1554
cpqAmperageProbeNormal	CPQIDA-MIB	Info	\$3	1.3.6.1.4.1.674.0.1	Amperage probe has returned to a normal value.	6	1202
cpqProcessorDeviceStatusFailure	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Processor device status has detected a failure.	6	1604
cpqLogNormal	CPQIDA-MIB	Info	\$3	1.3.6.1.4.1.674.0.1	Log size is no longer near or at capacity.	6	1552
cpqSystemPeakPowerNewPeak	CPQIDA-MIB	Info	\$3	1.3.6.1.4.1.674.0.1	System peak power sensor has detected a new peak value.	6	1013
cpqDeviceAdd	CPQIDA-MIB	Info	\$3	1.3.6.1.4.1.674.0.1	Device added to system.	6	1651
cpqBatteryNormal	CPQIDA-MIB	Info	\$3	1.3.6.1.4.1.674.0.1	Battery has returned to normal.	6	1702
cpqTemperatureProbeNormal	CPQIDA-MIB	Info	\$3	1.3.6.1.4.1.674.0.1	Temperature probe has returned to a normal value.	6	1052
cpqMemoryDeviceFailure	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Memory device status is critical.	6	1404
cpqACPowerCordNormal	CPQIDA-MIB	Info	\$3	1.3.6.1.4.1.674.0.1	AC power cord has regained power.	6	1502
cpqAmperageProbeWarning	CPQIDA-MIB	Warning	\$3	1.3.6.1.4.1.674.0.1	Amperage probe has detected a warning value.	6	1203
cpqTemperatureProbeNonRecoverable	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Temperature probe has detected a non-recoverable value.	6	1055
cpqVoltageProbeFailure	CPQIDA-MIB	Critical	\$3	1.3.6.1.4.1.674.0.1	Voltage probe has detected a failure value.	6	1154
cpqTemperatureProbeWarning	CPQIDA-MIB	Warning	\$3	1.3.6.1.4.1.674.0.1	Temperature probe has detected a warning value.	6	1053

Search results: 53 traps found

The **Edit Traps** grid shows all the traps that match the filter criteria and allows modification of multiple traps in the grid before saving the changes to OME. You can also add severity configuration for By Varbind Value severity or edit severity of variables for traps which already have severity as By Varbind Value. Once the edited changes are saved to OME, you can see the modified trap definition by navigating to **Manage >> Alerts >> Alert Categories**.

#### Note:

Events received in OME prior to editing the trap definition by using **Edit Trap** view will not be affected. Events received after the edited trap definition is saved will be classified based on the modified trap definition in OME.

## Reset Built-In Trap Definitions

The **Reset Trap** view allows you to revert the trap definitions of predefined traps, which were edited using the **Edit Trap** view, to their original state. The **Reset Trap** view grid lists all the pre-defined traps that were edited. You can filter the traps list in the **Edited Traps** grid by entering the Trap Name or Enterprise OID in the Trap Name or Enterprise OID field of respective column filter option. The grid allows the selection of multiple traps for reverting their trap definition as shown in Figure 15. When you click **Revert Traps**, the selected trap definitions will be reverted in OME to their original state after your confirmation. The status bar will display a message indicating the number of traps that were successfully reverted in OME. After the selected traps are reverted in OME, you can see the reverted (original) trap definition by navigating to **Manage >> Alerts >> Alert Categories & Definitions**.

### Note:

- Events received in OME prior to reverting the trap definition by using **Reset Trap** view will not be affected. OME will classify the events received thereafter using the reverted trap definition.
- Only predefined traps in OME can be reverted using **Reset Trap** view. The history of edited traps is not maintained and the traps can be reverted to their original state only.

Figure 15. Reset Trap View

The screenshot displays the 'Reset Built-in Trap Definitions' interface. On the left is a navigation pane with a tree structure including 'Common Tasks', 'Alert Logs', 'Alert Actions', 'Alert Categories & Definitions', 'Manage MIBs', 'Manage Traps', 'Custom Trap Definitions', and 'Reset Built-in Trap Definitions' (which is selected). The main area is titled 'Reset Built-in Trap Definitions' and includes a sub-header 'Edited Traps'. Below this is a table with the following data:


Name	Category Name	Severity	Enterprise OID	Format String	Description	Generic Trap ID	Specific Trap ID
pcEnvMonFanStateChange	Environmental	Info	1.3.6.1.4.1.89	Trap indicating the fan state. \$1	Dell PowerConnect PC-33.xx.pcEnvMonFanStateChange Trap	6	176

At the bottom right of the main area is a button labeled 'Revert Traps'.

## Imported HP Server Traps in OME

After you import the trap definitions in OME, you can view them by navigating to **Manage >> Alerts >> Alert Categories & Definitions**.

Figure 16. Imported Trap



The screenshot shows the OME (OpenManage Essentials) interface. The top navigation bar includes Home, Manage, Deployment, Reports, Settings, Logs, and Dell Solutions. Below this, a secondary bar shows Devices, Device Search, Discovery and Inventory, Alerts, System Update, Remote Tasks, and Configuration. The left sidebar contains a tree view under 'Alert Categories & Definitions' with various categories like Brocade-Switch, Compellent, CPQIDA-MIB, etc. The main pane displays a table titled 'Alert Categories' with a 'Name' column and a list of trap names.

Name
Brocade-Switch
Compellent
CPQIDA-MIB
Dell Advanced Infrastructure Manager
Environmental
EqualLogic Storage
FC-Switch
Firewall
Fluid Cache
Fluid Storage
General Redundancy
HyperV Server
IDRAC
Juniper-Switch
Keyboard-Video-Mouse (KVM)
Memory
Network
Other
PDU
Physical Disk
Power
Power Center
PowerEdge-C Server
Printers
Processor
Removable Flash Media
Security
Storage Enclosure
Storage Peripheral
Storage Software
System Events

## Import View Components

Figure 17. Import View

- **Browse and Select files for upload:** To choose the specific MIB.
- **Parse MIB:** To parse the MIB and extract trap definitions.

- **Category Name:** This list includes all the category names present in the OME. It allows you to change category names of the parsed trap definitions before you import them in OME. You can select any of the predefined categories or use the newly created category name (default selection). The MIB module will be new category name (in the earlier example it is CPQIDA-MIB).
- **Apply the selected event category to all traps:** This check box (selected by default) will help you to change the category name for the parsed trap definitions. The “Traps” grid allows multiple row selections. If you have selected a few rows in the grid and this check box is not selected, changing the category name from the drop-down list will change category name only for the selected rows. If this check box is selected, then changing category name from the list box will update category name for all the rows.

Category Name:  ☒ Apply the selected event category to all traps

**Note:** This check box overrides any selection/modification you have done in the grid. If you want to keep those changes ensure that this check box is deselected before you import data to OME.

- **Severity:** This list contains all the severity levels defined in OME. It allows you to change the severity of the parsed traps before you import them in OME.
- **Apply the selected severity to all traps:** This check box (selected by default) helps you to change the severity for the parsed trap definitions. The “Traps” grid allows multiple row selections. If you have selected a few rows in the grid and this check box is not selected, changing the severity by using the drop-down list will change the severity only for the selected traps. If this check box is selected, then changing the severity by using the drop-down list will update the severity for all the rows.

Severity:  ☒ Apply the selected severity to all traps

**Note:** This check box overrides any individual selection/modification you have done in the grid. If you want to keep those changes ensure that this checkbox is unselected before you import data to OME.

- **Trap:**
  - **Various Grid Columns**




Figure 18. Traps Grid

Traps Available for Import								
Drag a column header and drop it here to group by that column								
Name	Category Name	Severity	Format String	Enterprise OID	Description	Generic Trap ID	Specific Trap ID	
cpqSDCardDeviceFailure	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	SD card device has detected a failure.	6	1	
cpqBatteryFailure	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	Battery has detected a failure.	6	1704	
cpqBatteryWarning	CPQIDA-MIB	Warning	\$3	.1.3.6.1.4.1.674.0.1	Battery has detected a warning.	6	1703	
cpqBatteryNormal	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Battery has returned to normal.	6	1702	
cpqDeviceConfigError	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	Device configuration error detected.	6	1653	
cpqDeviceRemove	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Device removed from system.	6	1652	
cpqDeviceAdd	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Device added to system.	6	1651	
cpqProcessorDeviceStatusFailure	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	Processor device status has detected a failure.	6	1604	
cpqProcessorDeviceStatusWarning	CPQIDA-MIB	Warning	\$3	.1.3.6.1.4.1.674.0.1	Processor device status has detected a warning.	6	1603	
cpqProcessorDeviceStatusNormal	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Processor device status has returned to normal.	6	1602	
cpqLogFull	CPQIDA-MIB	Critical	\$3	.1.3.6.1.4.1.674.0.1	Log size is at capacity.	6	1554	
cpqLogWarning	CPQIDA-MIB	Warning	\$3	.1.3.6.1.4.1.674.0.1	Log size is near capacity.	6	1553	
cpqLogNormal	CPQIDA-MIB	Info	\$3	.1.3.6.1.4.1.674.0.1	Log size is no longer near or at capacity.	6	1552	

- **Name:** Trap name.
- **Category Name:** Event categories where you want to define the trap definitions. This is an editable field. You can change the category name by using this drop-down list or use the earlier mentioned generic drop-down list.
- **Severity:** Event severity which you want to be displayed in the OME event console when the specific trap is received from the remote SNMP device. This is an editable field. You can change the severity using the drop-down list or use the earlier mentioned **Severity** drop-down list. You may see a new entry (**By Varbind Value**) in this drop-down list and selected by default if the MIB traps are enumeration-based variables. For additional information, see the “**Severity Configuration by Value**” section.
- **Format String:** This field helps OME to display the event description for the incoming SNMP alerts. OME parses the trap variables and replace those values in this format string. This is an editable field and you can remove the unwanted contents or variables from this field.
- **Enterprise OID:** Event SNMP Enterprise OID.
- **Generic Trap ID:** Event SNMP Generic OID.
- **Specific Trap ID:** Event SNMP Specific OID.
- **Category ID:** Unique number which is used internally.
- **Package ID:** Unique number which is used internally.
- **Description:** Trap description which is obtained from the MIB. This is different from Format String and OME does not use this to display the description for the received SNMP traps in the event console.

- **Filters:** Every column header has a built-in filter which can be used to view specific trap definitions.

Figure 19. Grid Column Filters



- **Import traps:** This will import all of the updated values in the grid and “Severity Configuration by value” for the specific traps.
- **Status Bar:** The status bar is displayed at the bottom of the window. The status of the last operation that was performed is reported by the status bar.

## Severity Configuration By Value

**Note:** This specific HP Server MIB (CPQIDA-MIB) has traps having trap variable-based severity. The **Severity Configuration By Value** window can be used for MIBs which have such trap definitions. The following is an example to explain this behavior.

An SNMP trap definition may have trap variables which determine the severity for that particular trap. This attempts to parse those trap variables and gives you the option to select one of those variables. After the trap is imported to OME, OME uses these specific trap variable values to determine the trap severity and classifies it in the console.

Example:

Figure 20. SNMP Trap Definition Example Showing Trap Variable Based Severity

```

DellStatus ::= INTEGER {
    other(1),           -- status is not one of the following:
    unknown(2),        -- status of object is unknown (not known or monitored)
    ok(3),              -- status of object is OK (normal)
    nonCritical(4),     -- status of object is noncritical (warning)
    critical(5),        -- status of object is critical (failure)
    nonRecoverable(6)   -- status of object is non-recoverable (dead)
}

alertCurrentStatus OBJECT-TYPE
    SYNTAX      DellStatus
    ACCESS      read-only
    STATUS      mandatory
    DESCRIPTION
        "5000.0010.0004 Current status of object causing the alert."
    ::= { alertVariables 4 }

alertSystemUp TRAP-TYPE
    ENTERPRISE  baseboardGroup
    VARIABLES { alertSystem,
                alertTableIndexOID,
                alertMessage,
                alertCurrentStatus,
                alertPreviousStatus,
                alertData }
    DESCRIPTION
        "Server Administrator has completed its initialization."

    ::= 1001

```

In Figure 20, the *alertSystemUp* trap has 6 variables. The *alertCurrentStatus* variables have 6 possible status values (defined by *DellStatus*). By default, the “By Varbind value” severity is selected instead of “Normal”. To open the **Severity Configuration by Value** window, double-click the severity grid cell. In Figure 21, the *alertSystemUp* trap has 2 possible trap variables which have associated status values. The trap variables are available in the **Select the variable** drop-down list. By default, the first variable (\$4 → *alertCurrentStatus*) is selected. The grid in the **Severity Configuration by Value** window displays the possible variable values (*DellStatus* enumeration values). By default, the severity for all these values is set to “Normal”, but you can change the severity as required and click “Ok” to save the changes.

Figure 21. Severity Configuration By Value Dialog Box - Trap Variables

Severity Configuration by Value : alertSystemUp

Severity Configuration by Value

Select the Variable: \$4

Drag a column header: \$4, \$5

Trap Variable	Severity	Object ID	Object Value
\$4	Normal	1	other
\$4	Unknown	2	unknown
\$4	Normal	3	ok
\$4	Critical	4	nonCritical
\$4	Critical	5	critical
\$4	Normal	6	nonRecoverable
\$5	Normal	1	other
\$5	Unknown	2	unknown
\$5	Normal	3	ok
\$5	Critical	4	nonCritical
\$5	Critical	5	critical
\$5	Normal	6	nonRecoverable

OK Reset Cancel

- **Severity:** Displays the severity of the trap variable values.
  - For example, for the “\$4” trap variable and Object Id “1”, you can update the severity to “Warning” and then imported the data to OME.
  - When *alertSystemUp* trap is received from the remote device by OME, OME will read the 4th variable of this trap, in this case *alertCurrentStatus*, and reads its value. If the value is “1” then OME displays the trap as a “Warning”.
- **Object Value:** Displays the possible enumerations string values. For example, DellStatus.
- **Object ID:** Displays the possible enumerations integer values. For example, values mentioned in (n) for DellStatus.
- **Trap Variable:** Displays the enumerations based variables that are part of the trap. For example, *alertCurrentStatus* and *alertPreviousStatus*.

Figure 22. Severity Configuration By Value Dialog Box - Severity Selection

Severity Configuration by Value : alertSystemUp

Severity Configuration by Value

Select the Variable: \$4

Drag a column header and drop it here to group by that column

Trap Variable	Severity	Object ID	Object Value
\$4	Normal	1	other
\$4	Unknown	2	unknown
\$4	Info	3	ok
\$4	Normal	4	nonCritical
\$4	Warning	5	critical
\$4	Critical	6	nonRecoverable
\$5	Normal	1	other
\$5	Unknown	2	unknown
\$5	Normal	3	ok
\$5	Critical	4	nonCritical
\$5	Critical	5	critical
\$5	Normal	6	nonRecoverable

OK Reset Cancel

**Note:**

- Only one variable can be selected for *By Varbind value* based severity.
- The last saved values will be consumed while importing the trap definitions in OME.
- Re-opening the window will show the default values and not the last saved values. The last saved values are present in the background unless you reopen the severity window.
- Severity values changes between various variables on this window will not be saved if you select different variables from the list box.

## Parsing MIBs Containing Novel NMS Comments

**Note:** This specific HP Server MIB (CPQIDA-MIB) contains NMS comments for its trap definitions. This section can be used for MIBs which have NMS comments. The following section includes an example to explain this behavior.

Some of the SNMP MIBs may contain NMS comments along with the trap definitions. This will consume them to select the default severity for those traps and format string. In Figure 23, NMS comments can be seen between DESCRIPTION and specific trap Id (::= 1001).

**Note:** If you have traps having both NMS comments and enumeration-based trap variables, NMS will take the priority. You can still select *By Varbind value* severity for those traps from the **Severity** dropdown list for those specific traps.

Figure 23. Trap Definition Containing NMS Comments

```
alertSystemUp                                TRAP-TYPE
    ENTERPRISE baseboardGroup
    VARIABLES { alertSystem,
                alertTableIndexOID,
                alertMessage,
                alertData }
    DESCRIPTION
    "Server Administrator has completed its initialization."

    --Novell NMS trap annotation
    --#TYPE      "Server Administrator Startup Complete"
    --#SUMMARY   "%s"
    --#ARGUMENTS {2}
    --#SEVERITY  CRITICAL
    --#TIMEINDEX 99
    --#STATE     OPERATIONAL

    ::= 1001
```

OME decides the severity based on the "--#SEVERITY" field and the format string is formed with the "--#SUMMARY" and "--#ARGUMENTS" fields.


**Note:**

- Currently, OME considers only 1 variable in the format string.
- 2<sup>nd</sup> argument means \$3 for OME (refer to the earlier snapshot).

## HP Server MIB Module Definition and Reference MIBs

If you open the CPQIDA-MIB.mib file in a text editor, the following contents are displayed at the top section.

Figure 24. HP Server MIB



- **MIB Module Name:** This is the actual MIB name for CPQIDA-MIB.mib file. This becomes the new Event Category name when you parse this MIB.
- **Reference MIBs:** These are the MIBs that are required to compile and parse the CPQIDA-MIB.mib.

## Learn More

Visit [www.delltechcenter.com/ome](http://www.delltechcenter.com/ome)