



PowerEdge FX2 Enclosure

The Dell PowerEdge FX2 enclosure is the uniquely small modular foundation for the PowerEdge FX architecture, an extremely flexible and efficient platform for building an IT infrastructure that precisely fits your computing needs.

The PowerEdge FX2 is a 2U hybrid rack-based computing platform that combines the density and efficiencies of blades with the simplicity and cost benefits of rack-based systems.

Flexible configurations, more choice

The FX architecture's innovative modular design supports IT resource building blocks of varying sizes (compute, storage, networking and management) so data centers have greater flexibility to construct their infrastructures. The FX architecture includes the following server nodes and storage block:

- **PowerEdge FC830:** 4-socket scale-up server with unprecedented density and expandability
- **PowerEdge FC630:** 2-socket shared infrastructure workhorse
- **PowerEdge FC430:** quarter-width, 2-socket server with outstanding density
- **PowerEdge FM120x4:** world's first enterprise-class microserver
- **PowerEdge FD332:** ultimate dense direct-attached storage with unprecedented flexibility

The FX2 chassis has two versions:

- **PowerEdge FX2s:** "switched" configuration supporting up to eight low-profile PCIe 3.0 expansion slots
- **PowerEdge FX2:** lower-cost "unswitched" configuration that does not offer expansion slots.

The FX2 enclosure also offers I/O modules to several I/O aggregators that can simplify cabling, improve East/West traffic within the server, and enable LAN/SAN convergence — reducing cost and complexity.

The efficiencies of shared infrastructure

The FX2 enclosure allows servers and storage to share power, cooling, management and networking. It houses redundant power supply units (2000W, 1600W or 1100W) and eight cooling fans. The FX2's compact flexible design, the FX2 lets you simply and efficiently add resources when and where you need them, so you can let demand and budget determine your level of investment.

Innovative management with intelligent automation

The Dell OpenManage systems management portfolio simplifies and automates server lifecycle management — making IT operations more efficient and Dell servers the most productive, reliable and cost effective. Dell's agent-free integrated Dell Remote Access Controller (iDRAC) with Lifecycle Controller makes server deployment, configuration and updates automated and efficient. Using Chassis Management Controller (CMC), an embedded component that is part of every FX2 chassis, you'll have the choice of managing server nodes individually or collectively via a browser-based interface.

OpenManage Essentials provides enterprise-level monitoring and control of Dell and third-party data center hardware, and works with OpenManage Mobile to provide similar information on smart phones. OpenManage Essentials now also delivers server configuration management capabilities that automate bare-metal server and OS deployments, replication of configurations, and ensures ongoing compliance with set system configurations.

PowerEdge FX2, the foundation of Dell's revolutionary approach to converged infrastructure, combines blade density and efficiency with the cost advantages of rack servers.

Feature	PowerEdge FX2 technical specification
Chassis enclosure	Form factor: <ul style="list-style-type: none"> 2U chassis in height Dimensions: <ul style="list-style-type: none"> H: 8.68 cm (3.41 in) W: 43.35 cm (17.06 in) without rack ears; 48.19 cm (18.97 in) with rack ears D: 85.16 cm (33.52 in)
Server node options	PowerEdge FC830: Full-width: up to 2 FC830 per FX2 chassis PowerEdge FC630: Half-width: up to 4 FC630 per FX2 chassis PowerEdge FC430: Quarter-width: up to 8 FC430 per FX2 chassis PowerEdge FM120x4: Half-width: up to 4 FM120 per FX2 chassis PowerEdge FD332 storage block: Half-width: up to 3 FD332 per FX2 chassis for support of up to 16 x SFF 2.5" storage devices
Power supplies	Hot-plug PSUs: 2000W, 1600W or 1100W AC in 1+1 redundant or 2+0 non-redundant configurations
Cooling	8 hot-swappable fans provide cooling to the I/O components in the system
Communications	2 pass-through module or choice of 3 networking FN I/O Aggregator modules <ul style="list-style-type: none"> Dell PowerEdge FN410S: 4 ports SFP+ Dell PowerEdge FN410T: 4 ports 10Gb Base-T Dell PowerEdge FN2210S: Either 2 ports 2/4/8G Fibre Channel (NPG mode) and 2 ports of SFP+ or 4 ports of SFP+ with reboot
I/O slots	FX2s configuration: Up to 8 x PCIe 3.0 I/O expansion slots (low profile/half-length)
Systems management	<ul style="list-style-type: none"> FX uses Chassis Management Controller (CMC) to manage all resources (server nodes and shared infrastructure) in a single web console OpenManage portfolio for FX supports local and remote management, consistent with other PowerEdge products CMC and iDRAC are available with either Enterprise or Express licensing to best suit specific management needs Server nodes each contain proven iDRAC8 with Lifecycle Controller for agent-free, automated systems management
Recommended support	Dell ProSupport Plus for critical systems or Dell ProSupport for premium hardware and software support for your PowerEdge solution. Consulting and deployment offerings are also available. Contact your Dell representative today for more information. Availability and terms of Dell Services vary by region. For more information, visit Dell.com/ServiceDescriptions .

End-to-end technology solutions

Reduce IT complexity, lower costs and eliminate inefficiencies by making IT and business solutions work harder for you. You can count on Dell for end-to-end solutions to maximize your performance and uptime. A proven leader in Servers, Storage and Networking, Dell Enterprise Solutions and Services deliver innovation at any scale. And if you're looking to preserve cash or increase operational efficiency, Dell Financial Services™ has a wide range of options to make technology acquisition easy and affordable. Contact your [Dell Sales Representative](#) for more information.**

Learn more at Dell.com/PowerEdge.

©2015 Dell Inc. All rights reserved. Dell, the DELL logo, the DELL badge, PowerEdge, and OpenManage are trademarks of Dell Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. This document is for informational purposes only. Dell reserves the right to make changes without further notice to any products herein. The content provided is as is and without express or implied warranties of any kind. **Leasing and financing provided and serviced by Dell Financial Services L.L.C. or its affiliate or designee ("DFS") for qualified customers. Offers may not be available or may vary in certain countries. Where available, offers may be changed without notice and are subject to product availability, credit approval, execution of documentation provided by and acceptable to DFS, and may be subject to minimum transaction size. Offers not available for personal, family or household use. Dell and the DELL logo are trademarks of Dell Inc.

August 2015 | Version 2.0
Dell_PowerEdge_FX2_SpecSheet

